



IDEAL SUPPLY, INC.



11400 Kreutzer Rd.
Huntley, IL 60142

Ph. (847) 961-5900 Fx. (847) 961-5300
Email: illidealsupply@aol.com

624 Innovation Dr
Chesapeake, VA 23320

Ph. (757) 548-8050 Fx. (757) 548-8051
Email: vaidealsupply@aol.com

Point Styles for Screws such as: Machine Screws, Thread Cutting Screws, Tapping Screws, Sheet Metal Screws, and Thread Forming Screws




TYPE A POINT: A thread forming screw for use in thin metal .015 to .050 thick. Used with drilled, punched or nested holes in sheet metal, resin impregnated plywood, asbestos combinations, among others.



TYPE B POINT: A thread forming screw for use in heavier metal .050 to .200 thick. Larger root diameter with finer thread pitch for light and heavy sheet metal non-ferrous castings, plastics, impregnated plywoods, asbestos combinations, and other materials.



TYPE AB POINT: A thread forming screw combining locating type point of Type A with thread size and pitch of Type B. Normal limitations of Type B apply.



TYPE C POINT: A thread forming screw with either coarse or fine pitch machine screw thread and blunt tapered point. Eliminates chips and permits replacement with standard screw in the field. Higher driving torque required. Usable in heavy sheet metal and die castings.



TYPE U POINT: A thread forming screw with high Helix thread for driving or hammering into sheet metal, castings, fiber or plastics for permanent, quick assemblies.



TYPE F POINT: a thread cutting screw with machine screw thread with blunt tapered point, having multi-cutting edges and chip cavities. For heavy gauge sheet metal, aluminum, zinc and lead die castings, cast iron, brass and plastic.



TYPE FZ POINT: A thread cutting screw with machine screw with machine screw thread with blunt tapered point, having multi-cutting edges and chip cavities. For plastics, die castings, metal clad and resin impregnated plywoods, and asbestos. Also known as a BF.



TYPE 1 POINT: A thread cutting screw with single flute for general use. Produces a fine standard machine screw thread for field replacement. Also known as a D.



TYPE 17 POINT: A thread cutting screw for wood with a coarse tapping screw thread and a special long sharp point fluted to capture chips



TYPE 23 POINT: A thread cutting screw in the fine thread series offering maximum thread cutting area and excellent chip clearing, with minimum tightening torques. Also known as a T.



TYPE 25 POINT: A thread cutting screw similar to Type 23 point except with coarse Type B thread. For plastics and other soft materials with large chip clearing and cutting edges. Also known as a BT.



SELF-DRILLING: With special drilling points—lengths—diameters that will drill through 1/4" metal. Eliminates all hole preparation—drills faster than a drill. No punching, drilling or tapping required. Reduces die costs. Also known as a TEK® screw.